

Число и номинальное сечение жил, мм <sup>2</sup>	Наружный диаметр кабеля, мм		Масса 1 км кабеля, кг		Число и номинальное сечение жил, мм <sup>2</sup>	Наружный диаметр кабеля, мм		Масса 1 км кабеля, кг	
	0,66 кВ	1 кВ	0,66 кВ	1 кВ		0,66 кВ	1 кВ	0,66 кВ	1 кВ

Кабели марки ВВГнг-LS с круглыми жилами					Кабели марки АВВГнг-LS с круглыми жилами				
2 x 1.5	7.6	8.4	97	113	2 x 2.5	8.4	9.8	96	128
2 x 2.5	8.3	9.7	126	158	2 x 4	10.3	11.5	146	180
2 x 4	10.3	11.5	194	227	2 x 6	11.3	12.5	176	212
2 x 6	11.3	12.5	249	285	2 x 10	13.6	14.0	259	273
2 x 10	13.7	14.1	386	400	2 x 16	15.5	15.9	343	359
2 x 16	16.7	17.1	588	606	2 x 25	20.0	20.4	615	638
2 x 25	20.4	20.8	951	975	2 x 35	22.0	22.4	753	778
2 x 35	22.4	22.8	1211	1237	2 x 50	26.4	26.8	1089	1120
2 x 50	26.4	26.8	1666	1697	2 x 70*		29,8		1408
2 x 70*		29,8		2253	2 x 95*		34,4		1869
2 x 95*		34,4		3035	2 x 120*		37,4		2223
2 x 120*		37,4		3679	2 x 150*		43,4		2874
2 x 150*		43,4		4705	2x 185*		48,3		3557
2 x 185*		48,0		5817					
					3 x 2.5	9.4	10.3	121	143
3 x 1.5	8.0	9.5	115	148	3 x 4	10.9	12.2	164	201
3 x 2.5	9.4	10.3	167	188	3 x 6	11.9	13.2	199	239
3 x 4	10.8	12.1	236	273	3 x 10	14.4	14.8	295	310
3 x 6	11.9	13.2	308	348	3 x 16	16.4	16.9	391	411
3 x 10	14.5	14.9	484	499	3 x 25	21.2	21.6	690	714
3 x 16	17.8	18.6	741	781	3 x 35	23.3	24.2	849	901
3 x 25	21.6	22.0	1185	1211	3 x 50	28.0	28.4	1229	1263
3 x 35	24.2	24.6	1551	1581					
3 x 50	28.0	28.4	2093	2128	3 x 2.5 + 1 x 2.5	10.2	11.2	140	165
					3 x 4 + 1 x 2.5	11.8	12.8	190	219
3 x 1.5 + 1 x 1	9.3	10.2	149	172	3 x 6 + 1 x 2.5	12.5	13.9	217	261
3 x 1.5 + 1 x 1.5	9.3	10.2	153	175	3 x 6 + 1 x 4	13.0	14.4	232	279
3 x 2.5 + 1 x 1.5	10.2	11.1	194	219	3 x 10 + 1 x 4	14.8	15.7	305	339
3 x 4 + 1 x 2.5	11.8	12.8	277	306	3 x 10 + 1 x 6	15.2	16.3	324	364
3 x 6 + 1 x 2.5	12.5	13.9	341	385	3 x 16 + 1 x 6	16.9	17.9	409	450
3 x 6 + 1 x 4	13.0	14.4	365	413	3 x 16 + 1 x 10	18.5	18.9	482	504
3 x 10 + 1 x 4	14.9	15.8	519	553	3 x 25 + 1 x 10	21.8	22.3	709	733
3 x 10 + 1 x 6	15.4	16.4	550	590	3 x 25 + 1 x 16	22.5	22.9	754	781
3 x 16 + 1 x 6	18.7	19.2	813	834	3 x 35 + 1 x 16	25.2	25.6	955	985
3 x 16 + 1 x 10	19.3	19.7	869	892	3 x 50 + 1 x 16	28.8	29.3	1265	1299
3 x 25 + 1 x 10	22.2	22.7	1267	1293	3 x 50 + 1 x 25	29.7	30.1	1344	1380
3 x 25 + 1 x 16	24.1	24.6	1429	1461	3 x 70 + 1 x 25*		32,6		1643
3 x 35 + 1 x 16	25.6	26.1	1729	1761	3 x 95 + 1 x 35*		37,7		2184
3 x 50 + 1 x 16	28.8	29.3	2224	2258	3 x 120 + 1 x 35*		41,0		2601
3 x 50 + 1 x 25	29.7	30.1	2365	2402	3 x 150 + 1 x 50*		48,2		3381
3 x 70 + 1 x 25*		32,6		3068	3 x 185 + 1 x 50*		53,1		4121
3 x 95 + 1 x 35*		37,7		4149	4 x 2.5	10.2	11.2	140	165
3 x 120 + 1 x 35*		41,0		5002	4 x 4	11.8	13.3	191	235
3 x 150 + 1 x 50*		48,0		6414	4 x 6	13.0	14.4	234	281
					4 x 10	15.8	16.3	348	367
4 x 1.5	9.3	10.2	153	175	4 x 16	18.5	18.9	488	510
4 x 2.5	10.2	11.1	201	226	4 x 25	23.3	24.1	813	866
4 x 4	11.8	13.2	287	331	4 x 35	26.0	26.5	1032	1064
4 x 6	13.0	14.4	379	427	4 x 50	30.7	31.2	1453	1498
4 x 10	15.9	16.4	600	619					

Кабели марки АВВГнг-LS с секторными жилами

4 x 16	20.0	20.4	945	970	3 x 50	28.5	1091
4 x 25	24.1	24.6	1494	1526	3 x 70	31.5	1348
4 x 35	26.5	27.0	1930	1965	3 x 95	35.4	1725
4 x 50	30.7	31.2	2606	2646	3 x 120	38.0	2017
<b>Кабели марки ВВГнг-LS с секторными жилами</b>					3 x 150	41.0	2365
3 x 50		28.5		1972	3 x 185	44.8	2851
3 x 70		31.5		2610	3 x 240	50.2	3581
3 x 95		35.4		3471	3 x 50 + 1 x 25	30.5	1219
3 x 120		38.0		4216	3 x 70 + 1 x 35	33.7	1507
3 x 150		41.0		5104	3 x 95 + 1 x 50	38.0	1952
3 x 185		45.1		6253	3 x 120 + 1 x 70	41.0	2318
3 x 240		50.2		8027	3 x 150 + 1 x 70	44.0	2667
					3 x 185 + 1 x 95	48.0	3251
3 x 50 + 1 x 25 3 x		30.7		2262	3 x 240 + 1 x 120	53.6	4066
3 x 70 + 1 x 35		33.7		2990			
3 x 95 + 1 x 50		38.0		3985			
3 x 120 + 1 x 70		40.9		4939	4 x 50	31.3	1336
3 x 150 + 1 x 70		44.0		5827	4 x 70	34.9	1701
3 x 185 + 1 x 95		48.2		7234	4 x 95	39.0	2144
3 x 240 + 1 x 120		53.6		9239	4 x 120	42.0	2528
					4 x 150	45.6	3024
4 x 50	31.3	31.5	2483	2512	4 x 185	49.2	3590
4 x 70		35.1		3386	4 x 240	55.4	4598
4 x 95		39.0		4472			
4 x 120		41.9		5460			
4 x 150		45.6		6675			
4 x 185		49.4		8126			
4 x 240		55.4		10526			

\* - выпускаются по техническому решению